

Self-Adhered Modified Bitumen Roof System

Flintlastic SA delivers the reliable protection of traditional modified bitumen roofing for a fraction of the labor, plus:

- No kettle, fumes, or burn risk
- · No torch or risk of fire
- · Reduced training requirement
- No building occupant disturbance
- · No mess or side lap bleed out
- Reduced insurance requirement
- Superior waterproofing under clay/concrete tile compared to other underlayment options



\*\*UL 2218 Class 4 Impact Resistance - Certain systems are UL classified as to impact resistance as described in the UL Roofing Materials and Systems Directory.

# Meet the family

Select the Flintlastic SA base, interply (optional) and cap sheet combination that meets your building, performance and warranty needs:

### Flintlastic SA NailBase

Nailable base sheet for plywood/OSB or lightweight insulating concrete

#### Flintlastic SA PlyBase

Self-adhered base ply or interply

#### Flintlastic SA MidPly

Premium self-adhered base ply or interply, for extended warranties

#### Flintlastic SA Cap

Workhorse cap sheet

## Flintlastic SA Cap FR\*\*

Fire and impact resistant cap sheet



# **Aesthetic Selection**

Flintlastic SA Cap is available in twelve colors designed and engineered to match our most popular shingle blends or clay/concrete tile<sup>1</sup>:





Moiré Black



# **Popular Systems**

MF = Mechanically Fastened, SA = Self-Adhered

# Don't forget the tools and accessories!

- 70 lb. roller, for field application
- FlintPrime® QD & FlintPrime Aerosol, primer for applicable substrates and metal details
- FlintBond® SBS-Modified Adhesive
  - Trowel Grade, for endlaps and details
  - Caulk Grade, for details

Warranty Duration	Insulation/Coverboard	Base	Cap (SA)
12 Years	Optional	SA NailBase (MF)	SA Cap/
15 Years	Optional	SA PlyBase <sup>2</sup> (SA)	SA Cap (FR)
20 Years	Optional	SA MidPly <sup>2</sup> (SA)	SA Cap CoolStar®/
25 Years	Double layer, 2nd layer adhered	SA MidPly (SA)	SA Cap (FR) CoolStar

<sup>&</sup>lt;sup>2</sup> Wood deck? CertainTeed recommends the use of Flintlastic SA NailBase as a base sheet and SA PlyBase and SA MidPly as interplies, however, when self-adhering a base layer over wood decks, priming is required; self-adhering over wood decks is not permitted by code in Miami-Dade County; check your local building code; at the end of the roofing membrane's life, roofing membranes self-adhered over wood decks will require replacement of the deck; self-adhering to resinous wood, such as pine, is prohibited; roof systems with base sheets self-adhered directly to wood roof decks quality for Integrity Roof System Limited Warranties only; Integrity Roof System NDL Limited Warranties and Sure Start™ Plus 5-STAR Warranties require the use of Flintlastic SA NailBase as a base sheet.

